



Slurry Buster[™]

Shore Pac[®] Polymer Breaker

Description: Slurry Buster[™] is an industrial grade liquid oxidizing agent used to breakdown Shore Pac[®] slurry. Slurry Buster[™] is supplied in plastic re-sealable pails. Slurry Buster[™] is a highly effective clean-up solution.

Recommended Use: Slurry Buster[™] mixes into the drilling slurry immediately and breaks the polymer backbone through oxidation. Water is the end result, ready for convenient disposal. It can also be added to pressure washer with water to spray down the work area deck, slurry hoses and other surfaces.

Characteristics:

- Maximum strength at 12.5% active ingredients.
- Breaks slurry faster for quick, efficient disposal.
- Economical and environmentally safe.
- Removes polymer effectively from surfaces.
- Does not foam.

Typical Properties:	Appearance	green-yellow liquid
	pH	9.0 – 10.0
	Specific Gravity	1.08 – 1.26
	Odor	Similar to chlorine
	Weight	9.8 lbs/gal

Mixing and Application: 3-5 gallons of Slurry Buster[™] per 3,000 gallons Shore Pac[®] slurry (For fast break) 1-2 gallons of Slurry Buster[™] per 3,000 gallons (For slow break 24 hours). Circulate entire volume of slurry by pumping to ensure complete oxidation of polymer molecules.

Packaging: 5-gal plastic pails, 36 pails per pallet. All pallets are plastic-wrapped.